

## ACTIVATED CARBON WATER FILTERS



**OPTIONAL:** Preloaded, skid mounted, prepiped, prewired, and packaged with service/backwash pumps.



### For Applications Such As-

Apartment Buildings • Boiler Feed Water • Cooling Towers • Car Wash  
Dairies • Factories • Laundromats • Motels • Nursing Homes  
Office Buildings • Resorts • Restaurants • R.O. Pretreatment • Schools

**Quality Products for Quality Water**

## Standard Features For Reliability, Performance, and Quality Assurance

Over the years, Marlo has built a reputation as an industry standard for high quality water treatment systems and equipment.

Marlo MFG Packaged Water Filters reflect that overall commitment to excellence, and are fabricated using field-tested designs with a proven record of service reliability.

The MFG Series provides the latest technology in fiberglass tanks with top mounted control valves, along with hardware standardization. Only the filter media needs to be changed to successfully treat various water problems.

- **Fiberglass Filter Tanks, Seamless Non-Metallic**  
Provides maximum corrosion resistance at one third the shipping weight of steel tanks.
- **Extended Warranty**  
Fiberglass filter tanks are covered by a 5 year extended warranty.
- **All Brass, Motor Driven Control Valve with 7 Day Selective Time Clock and Fully Adjustable Backwash Cycles**  
Eliminates problems caused by fluctuating water pressure and allows for simplified adjustments to handle those severe water problems.
- **Inlet / Outlet Service Connections of 1" thru 3"**  
Provides recommended service flow rates at minimal pressure loss.
- **Filter Media Bed**  
The filter media has been properly chosen and quality inspected to insure optimum performance.
- **Factory Assembled, Tested and Palletized Prior to Shipment**  
Eliminates shipping damage and lost cartons during transit.
- **Automatic Built-in Bypass**  
Provides service water during backwash period if required.
- **Self-Adjusting Backwash Controller**  
Requires no field adjustment regardless of water pressure.
- **Non-Clogging Underdrain System**  
Durable non-corrosive ABS fine slotted underdrain

## MFG Series Filter Specifications

### FILTER MEDIA

**ACA-** Activated Carbon- Granular activated carbon that through a unique, steam-activation process removes chlorine, dissolved organics and compounds which cause undesirable tastes and odors.

### ACA FILTERS

MODEL	Pipe Size Inches	SERVICE FLOW RATE				Backwash Flow Rate (G.P.M.)	Drain Size Inches	Tank Size Inches Dia. Ht.	Filter Media Quantity Cu. Ft.
		Normal / PSID (G.P.M.)		Peak / PSID (G.P.M.)					
ACA-10G	1	2	2	5	3	5.0	3/4	10 x 40	1
ACA-12G	1	4	3	8	4	8.0	3/4	12 x 52	2
ACA-12G	1 1/2	4	2	8	2	8.0	1	12 x 52	2
ACA-14G	1	5	3	10	4	10.0	3/4	14 x 65	3
ACA-14G	1 1/2	5	2	10	2	10.0	1	14 x 65	3
ACA-16G	1	7	4	14	8	14.0	3/4	16 x 65	4
ACA-16G	1 1/2	7	2	14	5	14.0	1	16 x 65	4
ACA-18G	1	9	4	18	9	18.0	1	18 x 65	5
ACA-18G	1 1/2	9	2	18	5	18.0	1	18 x 65	5
ACA-21G	1 1/2	12	3	24	7	24.0	1 1/2	21 x 62	7
ACA-21G	2	12	2	24	3	24.0	1 1/2	21 x 62	7
ACA-24G	1 1/2	15	3	30	6	31.0	1 1/2	24 x 71	10
ACA-24G	2	15	2	30	3	31.0	1 1/2	24 x 71	10
ACA-30G	2	25	4	50	8	48.0	2	30 x 72	15
ACA-30G	3	25	2	50	4	48.0	2	30 x 72	15
ACA-36G	2	35	5	70	10	70.0	2	36 x 72	20
ACA-36G	3	35	2	70	5	70.0	2	36 x 72	20
ACA-42G	2	50	10	100	20	95.0	3	42 x 72	30
ACA-42G	3	50	4	100	8	95.0	3	42 x 72	30

### QUALITY ASSURANCE

All MARLO units are engineered and thoroughly tested to provide years of trouble-free performance with a minimum of maintenance. All components are factory tested and inspected.

### OPERATING SPECIFICATIONS

Pressure Range - 30 to 125 psi  
 Water Temperature - 110 °F Max  
 Electrical Rating - 120 V, 60 Hz, 10 Watts  
 - 220 V, 50 Hz, 10 Watts available on request  
 (Check with factory for other conditions)

### AVAILABLE OPTIONS

- No Raw Water Bypass - To eliminate raw water bypass during backwash and rinse cycle.
- Separate Source Backwash - Backwash water to be supplied from a different source than service water.
- Extra Cam and Switch - Dry contacts for control of auxiliary equipment and to provide interlock between filters to prevent them from backwashing at the same time.
- D.P. Initiation - Backwash initiated based on differential pressure across the media bed vs. time clock.
- Skid Mounted - Multiple filters can be mounted on structural steel skid with all interconnecting piping included.



Distributed in this area by:  
 FILTERS, WATER & INSTRUMENTATION, INC.  
 23 Londonderry Road | Unit 13  
 Londonderry, NH 03053-3314  
 Phone: (603) 434-9577 | Fax: (603) 434-2832  
[www.FiltersWater.com](http://www.FiltersWater.com)